

## FDA PU TIMING BELT WITH FDA SILICONE COVER

**Application field:** packaging and paper industry

**Advantages:** long life-span  
good adhesion  
excellent abrasion resistance  
optional direction of rotation

**Application:** pulling-off belts of VFFS packaging machines



Type:	Tooth Profile:	Length (mm)	Max Width W (mm)	Cord reinforcement:	Grinding on tooth side: (mm)	Coating (max-min) (mm)	Coating (ShA)	Optional Vacuum Constr.:	P (mm)	Alfa/R (°/mm)	H1 (mm)	H2 (mm)
T2,5-330	T2,5	330	60	Kevlár		2-3	25-40	-	2,5	40 °	0,7	0,6
T5-455	T5	455	60	SS		2-3	25-40	-	5	40 °	1,2	1
T5-500	T5	500	50	SS		3-6	25-40	-	5	40 °	1,2	1
T5-560	T5	560	50	SS		3-6	25-40	-	5	40 °	1,2	1
T5-610	T5	610	50	SS		3-6	25-40	-	5	40 °	1,2	1
T5-630	T5	630	60	SS		2-6	25-40	-	5	40 °	1,2	1
T5-690	T5	690	50	SS		3-6	25-40	-	5	40 °	1,2	1
T5-720	T5	720	40	SS		3-6	25-40	-	5	40 °	1,2	1
AT5-420	AT5	420	50	SS		3-6	25-40	-	5	50 °	1,2	1,5
T10-630	T10	630	60	kevlár	optional	2-6	25-40	A, B, C, H	10	40 °	2,5	2
T10-700	T10	700	50	kevlár	optional	3-6	25-40	A, B, C, H	10	40 °	2,5	2
T10-780	T10	780	50	kevlár	optional	3-6	25-40	A, B, C, H	10	40 °	2,5	2
T10-920	T10	920	50	kevlár	optional	3-6	25-40	A, B, C, H	10	40 °	2,5	2
130 XL	XL	330,2	60	SS		2-3	25-40	-	5,08	40 °	1,32	1,22
150 XL	XL	381	50	SS		3-6	25-40	-	5,08	40 °	1,32	1,22
180 XL	XL	457,2	60	SS		2-3	25-40	-	5,08	40 °	1,32	1,22
240 L	L	609,6	50	SS		3-6	25-40	-	9,525	40 °	1,85	1,7

