

NEOPRENE TIMING BELT WITH LINATEX COVER

- Fields of use:** packaging industry
- Advantages:** long life-span
good adhesion
excellent abrasion resistance
optional direction of rotation
- Application sample:** pulling-off belts of FFS packaging machines



Type	Application sample	Pitch p (mm)	Length (mm)	Width (mm)	Cord reinforcement	Material of the basic belt	Color of the basic belt
T5-455 + 3Li		5	455	max 65	glass fiber	neoprene	black
T10-630 + 6Li	Rovema/ Kopas	10	630	25, 28, 30, 50	glass fiber	neoprene	black
T10-660 + 3Li	SZCS-25	10	660	max 50	glass fiber	neoprene	black
T10-700 + 6Li	Wolf	10	700	max 50	glass fiber	neoprene	black
T10-720 + 6Li	Altopack	10	720	max 40	glass fiber	neoprene	black
T10-780 + 6Li	Rovema	10	780	max 50	glass fiber	neoprene	black
T10-800 + 6Li		10	800	max 50	glass fiber	neoprene	black
T10-920 + 6Li		10	920	max 50	glass fiber	neoprene	black
T10-920 + 3.5Li	Bosch	10	920	50	glass fiber	neoprene	black
225L + 4,5Li	Hassia	9,525	571,5	25,4	glass fiber	neoprene	black
240 L + 6Li		9,525	609,6	max 50	glass fiber	neoprene	black
255 L + 6Li	FMC 700, Simionate	9,525	647,7	max 40	glass fiber	neoprene	black

Type	Grinding on tooth side (mm)	Coating (mm)	Coating (ShA)	Vacuum Constr.	Perforation	a	b	c	ØD	Ød	alfa	t (mm)
T5-455 + 3Li	optional	3	35	yes	C	-	-	-	-	-	-	-
T10-630 + 6Si	16	6	35	optional	B / C	-	-	-	12	4	90°	1,5p
T10-660 + 3Li	optional	3	35	yes	C	-	-	-	-	-	-	-
T10-700 + 6Li	optional	6	35	yes	C	-	-	-	-	-	-	-
T10-720 + 6Li	15	6	35	optional	A / C	6	20	2	-	6	45°	1,5p
T10-780 + 6Li	optional	6	35	yes	C	-	-	-	-	-	-	-
T10-920 + 6Li	optional	6	35	optional	A / C	6	28	2	-	5	30°	2p
T10-800 + 6Li	optional	6	35	yes	C	-	-	-	-	-	-	-
T10-920 + 3.5Li	14	3,5	35	optional	A / C	6	28	2	-	5	30°	2p
225L + 4,5Li	15	6	35	yes	C	-	-	-	-	-	-	-
240 L + 6Li	optional	6	35	yes	C	-	-	-	-	-	-	-
255 L + 6Li	optional	6	35	yes	C	-	-	-	-	-	-	-

