

# POLYURETHAN AND NEOPRENE TIMING BELT WITH RUBBER COVER

**Fields of use:** packaging industry

**Advantages:** long life-span  
good adhesion  
excellent abrasion resistance  
optional direction of rotation

**Application sample:** pulling-off belts of FFS packaging machines



Type	Application sample	Pitch (mm)	Length (mm)	Width (mm)	Cord reinforcement	Material of the basic belt	Color of the basic belt	Construction of PU basic belt
T5-455 + 3G		5	455	max 65	steel / kevlar	PU	blue	cord s. inside
T10-630 + 6G	Rovema / Kopas	10	630	25, 28, 30, 50	kevlar / glass	PU / rubber	red-brown / black	cord s. outside
T10-630 + 4G		10	630	max 50	kevlar / glass	PU / rubber	red-brown / black	cord s. outside
T10-660 + 3G	SZCS-25	10	660	max 50	steel / glass	PU / rubber	natur / black	cord s. inside
T10-700 + 6G	Wolf	10	700	max 50	kevlar	PU	red-brown	cord s. inside
T10-720 + 6G	Altopack	10	720	max 40	glass	rubber	black	-
T10-780 + 6G	Rovema	10	780	max 50	kevlar	PU	red-brown	cord s. outside
T10-920 + 6G		10	920	max 50	kevlar	PU	red-brown	cord s. outside
T10-920 + 3.5G	Bosch	10	920	50	kevlar	PU	red-brown	cord s. outside
225L + 6G	Hassia	9,525	571,5	25,4	glass	rubber	black	-
240L + 6G		9,525	609,6	max 50	kevlar / glass	PU / rubber	red-brown / black	cord s. inside
255 L + 6G	FMC 700, Simionate	9,525	647,7	max 40	kevlar / glass	PU / rubber	red-brown / black	cord s. inside

Type	Grinding on tooth side (mm)	Coating (mm)	Coating (ShA)	Vacuum constr.	Perforation type	a	b	c	ØD	Ød	alfa	t (mm)
T5-455 + 3G	optional	3	35	optional	- / C	-	-	-	-	-	-	-
T10-630 + 6G	16	6	35	optional	B / C	-	-	-	12	4	90°	1,5p
T10-630 + 4G	optional	4	35	yes	C	-	-	-	-	-	-	-
T10-660 + 3G	optional	3	35	optional	- / C	-	-	-	-	-	-	-
T10-700 + 6G	optional	6	35	yes	C	-	-	-	-	-	-	-
T10-720 + 6G	15	6	35	optional	A / C	6	20	2	-	6	45°	1,5p
T10-780 + 6G	optional	6	35	optional	B / C	-	-	-	12	4	90°	1,5p / 2p
T10-920 + 6G	optional	6	35	optional	B / C	-	-	-	12	4	90°	1,5p / 2p
T10-920 + 3.5G	14	3,5	35	optional	A / C	6	28	2	-	5	30°	2p
225L + 6G	15	6	35	optional	B / C	-	-	-	10	5	90°	1,5p
240L + 6G	optional	6	35	yes	C	-	-	-	-	-	-	-
255 L + 6G	optional	6	35	yes	C	-	-	-	-	-	-	-

