


SILICON INSERT COUPLING

- Application field:** Machine industry
- Advantages:** Balance of angular misalignment of shafts, balance of parallel misalignment of shafts, precise, steady transmission of swing, high torsional stiffness, electric isolation of the end of shafts
- Typical applications:** Joint of rotating sign givers, servo-drives




„S“-TYPE



Type	Bore sizes (mm)			Dimensions (mm)			Screw D1min.	Ang. offset (deg.) D2min.	Par.offset (mm) D1, D2 max.	Max. Torque (Nm) OD
	D1min.	D2min.	D1, D2 max.	OD	L	N				
NPS 4	4,4	5,8	10	19,1	26,5	6,5	M4	0,6	0.1	3
NPS 5	5.8	7,5	12,7	25,4	38,1	11	M5	1	0.15	5,7
NPS-6	5,8	9,8	19	31,8	57,2	16	M6	1,6	0.2	8

„C“-TYPE



Type	Bore sizes (mm)			Dimensions (mm)			Screw D1min.	Ang. offset (deg.) D2min.	Par.offset (mm) D1, D2 max.	Max. Torque (Nm) OD
	D1min.	D2min.	D1, D2 max.	OD	L	N				
NPC 4	4,4	5,8	10	19,1	26,5	6,5	M2,5	0,6	0.1	3
NPC 5	5.8	7,5	12,7	25,4	38,1	11	M4	1	0.15	5,7
NPC 6	5,8	9,8	16	31,8	57,2	16	M5	1,6	0.2	8

